

wittich & visser
scientific and meteorological instruments

WIRELESS ANEMOMETER WITH ALARMS FOR CONSTRUCTION SITES AND INDUSTRY

WV410XW





LIVEDATA
web interface

FEATURES

- extremely easy mounting due to wireless sensor and magnetic mounting (optional accessories)
- up to 500 m range with standard range sensor
- up to 1300 m range with extended range sensor
- built-in audible alarm and red/yellow alarm lights
- 4 programmable alarm relay outputs with ON and OFF delays
- 2-zone wind direction alarm
- backlit graphic LCD with large numbers
- Wi-Fi output for sending data to LIVEDATA web interface

HISTORY DISPLAYS




FUNCTIONS

- current wind speed
- wind direction
- bar graph for current wind speed
- bar graph for peak wind speed
- 8 h wind speed history graph
- 8 h alarm history graph
- temperature

APPLICATIONS

- crane applications
 - mobile cranes
 - tower cranes
 - bridge cranes
- lift applications
- all applications where wind alarm is needed
- remote wind monitoring and logging



wittich & visser

scientific and meteorological instruments

COMPATIBLE SENSORS:



WVS 010-1 (standard range WS sensor)
WVS 011-1 (extended range WS sensor)



WVSD 010-1 (standard range WVSD sensor)
WVSD 011-1 (extended range WVSD sensor)

ORDERING:

Display unit

- 1 **WV410XW/D** display unit

Sets with sensors included

- 2 **WV410XW/WVS** display unit, extended range WVS sensor, WiFi output
3 **WV410XW/WVSD** display unit, extended range WVSD sensor, WiFi output



1



2



3

Access to Navis LIVEDATA web interface:

FREE BASIC ACCESS (1 min data refreshing, 24h graphs, ...)

PAYABLE ADVANCED ACCESS (2 seconds data refreshing, up to 1 month graphs and data logging, ...)



OPTIONS

Wind tunnel certificated version available

OPTIONAL ACCESSORIES

- 1 External antenna with 4 m cable, magnetic mounting
2 YAGI antenna

MOUNTING ACCESSORIES


- 3 Display magnetic mounting assembly




1



2



3



TECHNICAL DATA

Wind speed measurement range:	0,6...50 m/s
Wind direction measurement range:	0°– 359° (6 ° graph resolution)
Temperature measurement range:	-30....+60 °C
Wind speed units:	m/s, km/h, knots, mph
Temperature units:	°C, °F
Wind speed averaging period:	selectable 2 s, 10 s, 30 s
Wind direction averaging period:	10 s
Wind speed resolution:	0,1 m/s
Wind direction resolution:	6°
Temperature resolution:	1°C
Wind speed accuracy:	+/- 2,5 %, calibration possible in 0,5% steps
Wind direction accuracy:	+/- 2,5°, adjustable offset +/- 180°
Temperature accuracy:	+/- 1°C
Communication frequency :	868 MHZ
Antenna input:	50 Ohm, SMA connector
Range:	
- with extended range sensor	up to 1300 m visible distance
- with Yagi antenna	3-4 x nominal range
Wi-Fi data transmission rate:	every 2 seconds
Wi-Fi transmission frequency:	2,4 GHz
Wi-Fi range:	Up to 20 meters. It can varies with type of Wi-Fi router.
LIVEDATA web interface URL:	http://www.navis-livedata.com
Operating voltage:	12 - 24 V DC
Power consumption:	500 mA
Temperature operating range:	-30 ... +60 °C
Outputs:	4 x relay, contact rating 2 A/24 V, programmable ON and OFF delays
Alarms:	adjustable max. alarm red light + continuous sound signal adjustable pre. alarm yellow light + interrupted sound signal
Sound signal (integrated buzzer):	85 dB/10 cm
Dimensions:	150 x 80 x 55 mm
Weight:	260 g
Analog signal outputs:	2 x 4...20 mA (not isolated, common ground with supply) 4 mA = 0 m/s (0°) 20 mA = programmable 10 - 50 m/s (359°)